

Product Bulletin

Concept® 203-OAP **FLEXIBLE GLOSS WHITE PVC** **Permanent Adhesive**

Concept® 203-OAP is a 75mic premium white gloss flexible calendared vinyl film coated with 200-5031 permanent gray acrylic pressure sensitive adhesive laminated to a 135gsm DSPE liner. This film is designed to accept a variety of solvent-based inkjet, Latex and UV curable inks common to wide format digital printing systems. Adhesive 200-5031 offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 135gsm liner offers excellent product layflat in a variety of ambient conditions.

Applications	Concept® 203-OAP is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.	
Thickness	Film	75mic
	Adhesive	25mic
	Liner	135gsm
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature	+4,4°Celsius
	Service temperature	-40°C to +82°C.
Expected Exposure	Up to 5 years.	
Adhesion	To stainless steel	16 N/25mm (FTM01)
	Individual values may vary. Test thoroughly for your specific application.	
Water Resistance	Good. Test if immersed.	
Humidity Resistance	Good	
Solvent Resistance	Good	
Storage Stability	One year shelf life when stored at 21°C and 50% relative humidity	
Product Series	E203OAP-54	1,37m x 50m
	E203OAP-60	1,52m x 50m
Recommendations	Completely evaporate ink solvents before application. Failure to do so may facilitate solvent penetration resulting in premature vinyl degradation	



Manufacturer of Pressure Sensitive Films, Traffic Graffiti Floor Advertising Films, Custom Coatings and Printing Inks.

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537

Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.