

# PRODUCT BULLETIN

## GF 290 - CHALKMARK™

### PRODUCT DESCRIPTION

GF 290 ChalkMark™ vinyl is a 125mic matte black chalkboard vinyl with a clear high-tack removable adhesive on a 135gsm liner. ChalkMark™ is commonly used to produce decorative vinyl graphics on vinyl cutting equipment and for covering large areas for menu boards or murals.

Applications:	GF 290 ChalkMark can be used to create promotion graphics, menu boards, point-of-purchase graphics and decorations for bedroom walls. ChalkMark™ is not designed for coated/sealed/treated stainless steel, brass or bronze surfaces.
Film Thickness:	125mic (Thickness variation +/- 10%)
Adhesive Thickness	25mic (Thickness variation +/- 10%)
Liner Thickness	135gsm (Thickness variation +/- 10%)
Temperature Ranges:	Minimum application temperature +4,4°Celsius Service temperature -40°C to +93°C.
Expected Exterior Exposure:	Interior application only.
Adhesion:	To stainless steel 16 N/25mm (FTM01) Individual values may vary. Test thoroughly before production.
Removability:	ChalkMark will remove cleanly from smooth painted drywall and most surfaces for up to 1 year. (Under normal conditions)
Water Resistance:	Excellent
Humidity Resistance:	Excellent
Storage Stability:	One year shelf life when stored at 21°C and 50% relative humidity.
Product Codes:	E290-54 1,37m x 50m E290-60 1,52m x 50m

**GF General Formulations GmbH | Hansestraße 105 | 51149 Köln | Germany**

**Phone: +49 2203 59182-55 | Email: [info@gf.international](mailto:info@gf.international) | Web: <http://www.gf.international>**

# PRODUCT BULLETIN

## Recommendations:

GF 290 ChalkMark™ is compliant with CPSIA 2008, RoHS and REACH. GF 290 ChalkMark™ vinyl works with \*standard chalk, soft chalk, and liquid chalk markers.\*Please note that standard chalks vary and some may mar or scratch the vinyl surface due to their hardness and density, as well as the amount of pressure applied.

We recommend you test a small section of the film first. Soft chalk and Liquid Chalk Markers are ideal for this type of surface and will clean up with water and a damp cloth.

We do NOT recommend abrasive cleaners or strong chemicals as it will degrade the vinyl surface.

**GF General Formulations GmbH | Hansestraße 105 | 51149 Köln | Germany**

**Phone: +49 2203 59182-55 | Email: [info@gf.international](mailto:info@gf.international) | Web: <http://www.gf.international>**

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.