

Description

Gloss coloured soft PVC with high opacity. Excellent price-performance ratio (value for money).

Liner

Clay coated kraft paper 120gr/sqm.

Adhesive

Permanent, solvent-free Acrylic adhesive.

Application

Individual design solutions indoors and outdoors. Effective and decorative lettering/signage on vehicles and glass surfaces. Product identification. Corporate Design.

Technical Data

Thickness (face film)*	75 µm
Face film	Monomeric, calendered opaque gloss PVC film
Adhesive	Permanent clear, solvent-free acrylic adhesive
Adhesive strength	≥ 15 N/25mm, acc. to FINAT/FTM1 (24h)
Release liner:	120 gsm special clay-coated silicone kraft paper with squared print for easy processing and positioning
Outdoor durability***	3-5 years (colours) / up to 2 years (metallic)
Application temperature	Min. +10° C (50° F)
Suitable Substrates	Flat and smooth surfaces. Substrates like (painted) steel, glass, acrylic, aluminium
Flammability [DIN 4102 B1]	flame-retardant (B1-certified)

* average ** in original packaging, at 20° C and 50% relative humidity *** normal climate of Central Europe

Note

Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material.

Safety and disposal

To be classified as "special industrial, not dangerous, waste" and therefore to be disposed of with urban solid waste at controlled waste dumps or incinerators.



X-film GmbH
Gerberstraße 2 51789 Lindlar Deutschland
Telefon +49.02266.477850
www.x-film.de sales@x-film.de

