


INTERNAL APPLICATION 95% OPACITY ANTI-HEAT

DESCRIPTION

Our black IR 95 film is perfect for darkening windows and protecting against the sun. It prevents excessive indoor heat and, above all, glare. For a long-lasting application, apply a sealant around the edge of the film.







USE: For all types of glazing.



MAINTENANCE: After 30 days with a standard cleaning solution (non-abrasive, ammonia-free, etc.). Do not use cleaning products that could scratch the surface.



STORAGE: 2 years from delivery. This film should be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet the highest standards, we recommend that you do not mix films from different productions

SOLAR FILM IR 95 CERAMIC FILM

SUPPORT: Vinyl

ADHESIVE: Acrylic polymer

Siliconized PET 23 microns **PROTECTOR:**

THICKNESS: 70 microns

Black **COLOUR: APPLICATION SIDE:** Internal

VISIBLE LIGHT TRANSMISSION: 4,3%

UV BLOCKING: 99 %

INFRARED REFLECTION: 79 %

APPLICATION T°: min, + 5°C

FIRE RATING: B-s1, d0

GUARANTEE:

*For glazing not exposed to the sun

BY ROLL:



1,52 x 30 m

2 / 3 years depending on exposure to the sun*

METHOD OF APPLICATION

The surface to be bonded must be free from dust, grease or any other contaminant. Some materials, such as polycarbonate, can cause bubbling problems. Α compatibility test is Can be therefore recommended. installed on plexiglass and polycarbonate.

PRODUCTION AND STANDARDS

In order to constantly improve our products, we may modify colours and manufacturing processes without prior notice. Before applying our films, we recommend that users ensure that they are suitable for the intended use and comply with current standards.

Application Note







Vidéo of the

pose

SCAN ME

: +33 (0)1 43 99 00 22

: info@reflectiv.com

: www.reflectiv.com

Showroom: 36 rue Réaumur 75003 Paris

Head office: P.A. des petits carreaux