Holographic Vinyl DATA SHEET

CONSTRUCTION			
PRODUCTION CONSTRUCTION	/ / / / / / / / / / / / /	SURFACE MATERIAL	
	★★★★★★★★★★★★	PRESSURE SENSITIVE ADHESIVE	
	/ / / / / / / / / / / / /	LINER	

SURFACE MATERIAL			
Article Name	PET Film (Laser)	Color	Laser/Holographic
Thickness	0.05 ± 5% mm	Smoothness	Good
Basic Weight	103 ± 5% g/m²	Weather Resistance	1 Year
Print Ability	See Note Below		

LINER			
Article Name	PE Lami Release Paper	Color	Colorful
Thickness	0.140 ± 0.008 mm	Smoothness	Good
Basic Weight	120 ± 6 g/m²	Die Cutting	Good
Tension Strength	9.0↑ g/15mm		

PRESSURE SENSITIVE ADHESIVE			
Adhesive Base	Acrylic	Release Force	7~15 g/25mm
Thickness	0.026 ± 0.002 mm	Holding Power	8↑ hr/kg·20mm²
Coating Weight	20 ± 2 g/m²	Weather Resistance	1 Year
Solvent Retention	2.5%↓	Temperature Range	-5~80℃
Initial Tack	10↑ No/Ball	Solvent Resistance	Good
180° Peel Adhesive	0.8↑ kg/25mm		

PRINT ABILITY		
	Solvent Ink	**NOT SUPPORTED**
	UV Ink (for Glass)	**SUPPORTED**

REMARK

Technical data are based on reliable experiments by the Company. They do not guarantee all properties completely as specified. Please study your purpose and conditions before application.